



Low profile design



Hi-Tech Cord ensures constant tension



Aluminium supports



Remote control operation

## Features Include

- Tension:** The fabric and front rail are kept under constant tension by means of a spring system, wheel runners and the Hi-Tech Cord.
- Runners:** Wheeled runner system ensures an almost noiseless smooth running front rail along the side tracks
- Material:** Fabricated from corrosion resistant materials. Headbox constructed from extruded aluminium.
- Finish:** Powdercoated to match existing framework.
- The Cord:** The Hi-tech Spectra Cord guarantees a long life for your conservatory awnings
- Sizes:**  
Minimum width per unit- 2 metres.  
Maximum width per unit- 5.5 metres.  
Maximum projection per unit- 6 metres.  
Maximum surface area per unit- 25 metres squared.  
Units can be joined together making the width almost unlimited.
- Quality:** 5 year guarantee. You can therefore expect that only the best materials were used and a high level of importance placed on providing the perfect finish.
- Operation:** The VZ520 are equipped with electrical operation, using a tubular motor. For the ultimate in comfort an automatic wind-sun sensor regulates the awning automatically, depending on the light intensity. Remote control provides optimal ease of operation and requires no wiring.

Harol® conservatory awnings combine a high quality of finish with modern styling and are suitable for assembly on any standard type of conservatory, pergola or outdoor construction. They are built entirely of corrosion resistant materials. When rolled up, the awning fabric is completely inside the box, protected against any effects of the weather outside. The box is fixed to the guide rails, which are fastened to the conservatory frame by means of fastening supports. These supports are available in your choice of aluminium or synthetic. The awning is kept at a set distance from the conservatory roof by the positioning of the guide rails and a cable-spring system that keeps the fabric under constant tension. A space is kept free between the side guide rails and the fabric in order to ensure good ventilation and heat dissipation.

## A solid guarantee of quality



Harol® conservatory awnings are manufactured from high-quality materials: solid, rustproof aluminium frames, synthetic components, rot and mildew resistant fabrics. Harol® gives you a **5-year quality guarantee** on its products!

**ISO 9001**  
certified company



The **Hi-Tech Cord** - developed specially for this product guarantees a long life for your conservatory awning.



The fabric and the front rail are kept under constant tension by way of a spring, wheel-runners and the Hi-Tech cord.

VZ520		Maximum width in meters																Maximum surface	Number of units	Number of motors	Dimensions - VZ520 Minimum width per unit: 2 m Maximum width per unit: 5.5 m Maximum projection: 6 m Maximum surface area per fabric section: 25 m <sup>2</sup>
Type	Number of units	1	2	3	4	5,5	6	7	8	9	10	11	12	13	16,5	22					
Type 1	1 unit			1 unit														25 m <sup>2</sup>	1	1	
Type 2	2 units					2 units												50 m <sup>2</sup>	2	1	
Type 3	3 units							3 units										75 m <sup>2</sup>	3	2	
Type 4	4 units									4 units								100 m <sup>2</sup>	4	2	